

Delphion

RESEARCH

INTEGRATED IAM

SERVICES

INSIDE DELPHION

[Log Out](#) | [Work Files](#) | [Saved Searches](#) | [My Account](#) | [Products](#) | [News](#) | [Events](#) | Search: [Quick/Number](#) | [Boolean](#) | [Advanced](#) | [Help](#)

## The Delphion Integrated View

Buy Now: [More choices...](#)Tools: Add to Work File: [Create new Work File](#) ☒ [Go](#)View: [INPADOC](#) | Jump to: [Top](#) ☒ Go to: [Derwent...](#)[Email this to a friend](#)

🔍 Title: **JP10050343A2: FLUORINE-CONTAINING SOLVENT FOR LITHIUM BATTERY WITH HIGH SAFETY**

🔍 Country: **JP Japan**

🔍 Kind: **A**

🔍 Inventor: **BESENHARD JUERGEN OTTO PROF DR;  
WERNER KONRAD VON DR;  
WINTER MARTIN DR;**

🔍 Assignee: **HOECHST AG**  
[News, Profiles, Stocks and More about this company](#)

🔍 Published / Filed: **Feb. 20, 1998 / May 12, 1997**

🔍 Application  
Number: **JP1997000121202**

🔍 IPC Code: **H01M 10/40;**

🔍 Priority Number: **May 13, 1996 DE1996019619233**

🔍 Abstract:

**PROBLEM TO BE SOLVED:** To enhance safety of an electrolyte-containing device and provide an electrolyte solution with viscosity and conductivity capable of being used even at low temperature by using a partially fluorinated aliphatic ether of the specified group as a solvent of an electrolyte system of a lithium secondary battery.

**SOLUTION:** An effective amount of at least one of partially fluorinated ether represented by formula I and/or at least one of partially fluorinated ether represented by formula II are/is added to an electrolyte system as a fluorine-containing solvent for a lithium battery with high safety. Formula I:  $\text{RO}-[(\text{CH}_2)_m]_n\text{-CF}_2\text{-CFH-X}$ , (R is a straight-chain alkyl group having 1 to 10 carbon atoms or a branched alkyl group having 3 to 10 carbon atoms, X is a perfluoroalkyl group having 1 to 6 carbon atoms allowed it to contain a fluorine atom, chlorine atom, or ether oxygen, m is an integer of 2-6, and n is an integer of 1-8.) Formula II:  $\text{X-CFH-CF}_2\text{-O}-[(\text{CH}_2)_m]_n\text{-CF}_2\text{-CFH-X}$  (X, m, and n are the same as the formula I).


**COPYRIGHT:** (C)1998,JPO

🔍 Designated **CH DE FR GB IT LI**


Country:

🔍 Family: [Show 4 known family members](#)

🔍 Forward  
References:

| PDF                                                                                 | Patent                    | Pub.Date   | Inventor        | Assignee         | Title                                                                            |
|-------------------------------------------------------------------------------------|---------------------------|------------|-----------------|------------------|----------------------------------------------------------------------------------|
|  | <a href="#">US6210835</a> | 2001-04-03 | Arai;<br>Juichi | Hitachi,<br>Ltd. | <a href="#">Lithium secondary battery and liquid electrolyte for the battery</a> |


🔍 Other Abstract **CHEMABS 128(05)050763H DERABS C1997-552597**



[View  
Image](#)

**1 page**

Info:



[Nominate this for the Gallery...](#)



(19)

(11) Publication number: **10050343 A**

Generated Document.

**PATENT ABSTRACTS OF JAPAN**(21) Application number: **09121202**(51) Intl. Cl.: **H01M 10/40**(22) Application date: **12.05.97**

|                                                                                                                                               |                                                                                                                                                                                       |
|-----------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| (30) Priority: <b>13.05.96 DE 96 19619233</b><br>(43) Date of application publication: <b>20.02.98</b><br>(84) Designated contracting states: | (71) Applicant: <b>HOECHST AG</b><br>(72) Inventor: <b>BESENHARD JUERGEN OTTO</b><br><b>PROF DR</b><br><b>WERNER KONRAD VON DR</b><br><b>WINTER MARTIN DR</b><br>(74) Representative: |
|-----------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

**(54) FLUORINE-CONTAINING SOLVENT FOR LITHIUM BATTERY WITH HIGH SAFETY**

(57) Abstract:

**PROBLEM TO BE SOLVED:** To enhance safety of an electrolyte-containing device and provide an electrolyte solution with viscosity and conductivity capable of being used even at low temperature by using a partially fluorinated aliphatic ether of the specified group as a solvent of an electrolyte system of a lithium secondary battery.

**SOLUTION:** An effective amount of at least one of partially fluorinated ether represented by formula I and/or at least one of partially fluorinated ether represented by formula II are/is added to an electrolyte system as a fluorine-containing solvent for a lithium battery with high safety.

Formula I:  $\text{RO}-[(\text{CH}_2)_m]_n\text{-CF}_2\text{-CFH-X}$ , (R is a straight-chain alkyl group having 1 to 10 carbon atoms or a branched alkyl group having 3 to 10 carbon atoms, X is a perfluoroalkyl group having 1 to 6 carbon atoms

allowed it to contain a fluorine atom, chlorine atom, or ether oxygen, m is an integer of 2-6, and n is an integer of 1-8.) Formula II:  $X-CFH-CF_2O-[(CH_2)mO]_n-CF_2-CFH-X$  (X, m, and n are the same as the formula I).

COPYRIGHT: (C)1998,JPO